Conforms to 1910.1200 Issued: May 18, 2018

FORMULA 55 FLOOR STRIPPER

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Formula 55 Floor Stripper Product Number: 564

Recommended Use: High Performance Floor Stripper Concentrate- dilute prior to use.

Product intended for commercial and industrial use only.

Uses Advised Against: Other than per labelled instructions

Supplier Address:

Nichols

1391 Judson Road

Norton Shores, MI 49456 Telephone: 800-442-0213 Internet: www.enichols.com

FOR CHEMICAL EMERGENCY: CHEMTEL 800-255-3924

24 HOUR EMERGENCY MEDICAL HELP

2: HAZARDS IDENTIFICATION

Classification: Skin Corrosion- Category 1B

Eye Damage - Category 1

Acute Toxicity - Inhalation - Category 4

Signal Word: DANGER

Pictogram:





Hazard Statements:

Causes severe skin burns and eye damage.

Causes serious eye damage.

Harmful if inhaled.

Precautionary Statements:

Do not breathe mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/eye protection/face protection.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Immediately call a POISON CENTER/doctor if you feel unwell.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Other Hazards: None known

Supplemental Information: None known

3: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Weight % *
ethylene glycol monobutyl ether	111-76-2	30 - 50
monoethanolamine	141-43-5	10 - 20

^{*} Exact concentration of the ingredients has been withheld as a trade secret.

Conforms to 1910.1200 Issued: May 18, 2018

FORMULA 55 FLOOR STRIPPER

4: FIRST AID MEASURES

DECRIPTION OF FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eye with plenty of water for at least 15 minutes. (If easy to do, remove

contact lenses, if worn). Seek medical attention.

Skin Contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing

contaminated clothing and shoes. Seek medical attention.

Inhalation: If breathing is difficult. Remove subject to fresh air. Seek medical attention immediately.

Ingestion: Call a physician or poison control center. Do not induce vomiting. Seek medical advice immediately.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye Contact: Causes eye burns.

Skin Contact: Causes skin burns.

Inhalation: Harmful if inhaled. May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion: May cause burns and irritation to mouth, throat and stomach.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Treat symptomatically.

5: FIRE-FIGHTING MEASURES

Suitable Extinguishing media: Water spray, CO₂, dry chemical, alcohol-type or universal type foams

<u>Specific Hazards:</u> Corrosive liquid. (See Sections 8 and 10.) Do not spray a solid stream of water or foam

directly in hot liquid. This may cause frothing.

<u>Protective Equipment and Precautions:</u> Fire fighters should wear NIOSH approved breathing apparatus. Materials

can splatter above 100° C / 212° F

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Put on personal protective equipment (see Section 8). Keep spectators away. Floors

may be slippery: use care to avoid falling.

Environment Precautions: Keep spills and cleaning run-off out of sewers and open bodies of water.

CONTAINMENT AND CLEAN-UP

Small Spills: Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance

with local, state and federal regulations.

Large Spills: Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery

or disposal and solid diking material to separate containers for disposal.

Waste Disposal: Landfill or incinerate the contaminated solids and diking material in accordance with local, state and

federal regulations. Non-salvageable liquid should be drummed and disposed of in accordance with

local, state and federal regulations.

7: HANDLING AND STORAGE

<u>Precautions for Safe Handling:</u>
Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only

in well-ventilated areas. Avoid breathing vapors or mists. Remove and wash

contaminated clothing and footwear before re-use.

Conditions for Safe Storage: Storage temperature (Max. 60°C/140°F - Min. 1°C/34°F)

Other Information: Keep from freezing. Keep container sealed when not in use. Keep out of reach of

children.

8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

		ACGIH		OSHA	
Ingredient	CAS Number	TWA	STEL	TWA	STEL
ethylene glycol monobutyl ether	111-76-2	20 ppm (BEI)	N/L	50 ppm (skin)	N/L
monoethanolamine	141-43-5	3 ppm	6 ppm	3 ppm	N/L

Conforms to 1910.1200 Issued: May 18, 2018

FORMULA 55 FLOOR STRIPPER

Engineering Controls: Use only with adequate ventilation. Use local ventilation and other engineering controls to maintain

airborne contaminants below established and recommended exposure limits. If this product contains ingredients with exposure limits, monitoring may be required to determine the effectiveness

of ventilation and other control measures.

Personal Protective Equipment (PPE)

Eye/Face Protection: Safety eyewear is recommended, to avoid chemical splashes and mists.

Skin Protection: Chemical resistant gloves are recommended.

Respiratory Protection: Respiratory protection should be worn when there is a potential of inadequate ventilation. If

exposure limits are exceeded or symptoms are experienced, use an approved respirator.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety practice.

9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:clear blue, liquidOdor:floral fragranceOdor Threshold:data not available

pH: 11.5

Freezing Point: data not available
Boiling Point: data not available

Flash Point: $> 200^{\circ}F / > 93^{\circ}C$ (ASTM D56)

Evaporation Rate: less than water

Flammability (solid, gas):

Flammability limits:

Vapor Pressure:

Vapor Density:

not applicable to liquids
data not available
data not available
data not available

Relative Density: 7.98 lb/gal @ 68°F / 0.96 kg/l @ 20°C

Solubility: miscible in water
Partition Coefficient: data not available
Auto Ignition temperature: data not available
Decomposition Temperature: data not available
Viscosity: < 10 cps @ 68°F

VOC: 54.5% (as supplied), 10.5% (1:4), 5.8% (1:8)

10: STABILITY AND REACTIVITY

Reactivity:Not reactive under normal conditions.Stability:Stable under normal conditions.

Hazardous reactions: Adding water directly to the product may generate heat and cause product to splash. To avoid

adverse reaction, always add product to water, do not add water to product.

SPECIFIC EFFECTS

Conditions to avoid: Improper order of dilution. Do not mix with other chemicals unless stated on the product label.

Incompatible materials: Strong acids and oxidizing agents

Hazardous decomposition products: carbon monoxide, carbon dioxide and nitrogen oxides

11: TOXICOLOGICAL INFORMATION

Acute Toxicity: Not determined on product.

LOCAL EFFECTS

Can cause severe skin burns. Carcinogenicity: Skin contact: None known Can cause serious eye damage. Reproductive effects: Eye contact: None known Teratogenicity: None known Sensitization: None expected Chronic effects: None expected Mutagenicity: None known

Conforms to 1910.1200 Issued: May 18, 2018

FORMULA 55 FLOOR STRIPPER

COMPONENT INFORMATION

Component	LD50 Oral- Rat (mg/kg)	LD50 Dermal - Rabbit (mg/kg)	LC ₅₀ Inhalation- Rat (mg/l)	
ethylene glycol monobutyl ether	470	220	2.21 (4hr)	
monoethanolamine	1720	1025	N/A	

Carcinogenicity:

Component	IARC	NTP	OSHA
ethylene glycol monobutyl ether	IARC 3	N/L	N/L

12: ECOLOGICAL INFORMATION

Ecotoxicity: Ecological testing has not been completed on the mixture.

Persistence and Degradability:Data not available.Bioaccumulative Potential:Data not available.Mobility in Soil:Data not available.Other Adverse Effects:Data not available.

13: DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, regional and national regulations.

14: TRANSPORT INFORMATION

UN Number: UN1760

<u>UN Proper Shipping Name:</u> Corrosive liquid, n.o.s. (ethanolamine)

Hazard Class:8Packing Group:IIMarine Pollutant:NoneTransport in Bulk:N/A

<u>Other Information:</u> Package Volumes < 1L are shipped under Limited Quantity Exemption.

15: REGULATORY INFORMATION

U.S. REGULATIONS/REPORTING:

		SARA		
Ingredient	CAS Number	302/304	SARA 313	CERCLA
ethylene glycol monobutyl ether	111-76-2	N/L	1.00%	N/L

STATE RIGHT-TO-KNOW STATUS:

Ingredient	CAS Number	MA - RTK	NJ - RTK	PA - RTK	RI - RTK
ethylene glycol monobutyl ether	111-76-2	present	present	present	present
monoethanolamine	141-43-5	present	present	present	present

CALIFORNIA PROPOSITION 65: Components are not present on CA Prop 65 listing.

16: OTHER INFORMATION

Abbreviations Used:

N/A - Not applicable N/E - Not Established

N/L - Not Listed

IARC 3 - Unclassifiable as to carcinogenicity in humans.

Revision Information:

May 18, 2018 - SDS issue

Conforms to 1910.1200 Issued: May 18, 2018

FORMULA 55 FLOOR STRIPPER



Health: 3 Flammability: 0 Reactivity: 0

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) or the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnish of such information.

This SDS has been provided to you in accordance with the OSHA Hazard Communication Standard (29CFR1910.1200).

IMPORTANT SAFETY INFORMATIONDO NOT DISCARD**PLEASE ROUTE TO COMPANY SAFETY OFFICER**